


























Conduit selection table Anaconda Multiflex.

Multiflex	Material	Material	Temp. (°C)		Resistance (NEN-EN-IEC 61386)			Flexibility	Resistance		Approvals	Protection	Page
			Min.	Max.	Compr.	Impact	Tensile		UV	Oil			
 FCEN	Galvanised steel	-	-55	+300	4 (1250N)	4 (6J)	4 (1000N)	+++	++++	++++		IP 40	1-02
 SL	Galvanised steel	-	-55	+300	4 (1250N)	4 (6J)	4 (1000N)	+++	++++	++++		IP 40	1-06
 SLI	Stainless steel AISI-304	-	-100	+600	4 (1250N)	4 (6J)	4 (1000N)	+++	++++	++++		IP 40	1-07
 SLI-316	Stainless steel AISI-316	-	-100	+600	4 (1250N)	4 (6J)	4 (1000N)	+++	++++	++++		IP 40	1-08
 SLI-CAP	Stainless steel AISI-304	-	-100	+600	3 (750N)	3 (2J)	3 (500N)	++++	++++	++++		IP 40	1-16
 SLB	Galvanised steel with stainless steel braid	-	-55	+300	4 (1250N)	4 (6J)	4 (1000N)	++++	++++	++++		IP 40	1-19
 UIG	Galvanised steel	-	-55	+300	5 (4000N)	4 (6J)	4 (1000N)	++++	++++	++++		IP 40	1-21
 UI	Stainless steel AISI-304	-	-100	+600	5 (4000N)	4 (6J)	4 (1000N)	++++	++++	++++		IP 40	1-22
 UI-CAP	Stainless steel AISI-304	-	-100	+600	5 (4000N)	4 (6J)	4 (1000N)	++++	++++	++++		IP 40	1-37
 RWA	Aluminium	-	-45	+260	4 (1250N)	4 (6J)	3 (500N)	++	++++	++++	  	IP 40	1-41
 Anaflex	Stainless steel AISI-316L	-	-70	+250	3 (750N)	3 (2J)	4 (1000N)	++++	++++	++++	 	IP 69K	1-44

CONDUIT SELECTION TABLE

The fittings for Multiflex are outlined on the next page after the conduit and/or in chapter 5.

