









## Conduit selection table Anaconda Multitite.

Multitite	Material	Material	Temp. (°C)		Resistance (NEN-EN-IEC 61386)			Flexibility	Resistance		Approvals	Protection	Page
			Min.	Max.	Compr.	Impact	Tensile		UV	Oil			
 FCD Grey	Galvanised steel	PVC-RoHS	-20	+80	3 (750N)	3 (2J)	3 (500N)	++++	++	++		IP 67	2-02
 FCD Black	Galvanised steel	PVC-RoHS	-20	+80	3 (750N)	3 (2J)	3 (500N)	++++	++++	++		IP 67	2-03
 FCE Black	Galvanised steel	PVC-RoHS	-20	+80	4 (1250N)	4 (6J)	4 (1000N)	++++	++++	++		IP 67	2-04
 FCE-LFH Black	Galvanised steel	Polyolefin Halogen-free RoHS	-25	+80	4 (1250N)	4 (6J)	4 (1000N)	++++	++++	++		IP 67	2-05
 FCE-PU-V0 Black	Galvanised steel	Polyurethane Halogen-free RoHS	-50	+105	4 (1250N)	4 (6J)	4 (1000N)	++++	++++	++++		IP 67	2-06

## CONDUIT SELECTION TABLE

The fittings for Multitite are outlined on the next pages after the conduit.

