



































## Conduit selection table Anaconda Sealtite®.

### CONDUIT SELECTION TABLE

Sealtite	Material	Material	Temp. (°C)		Resistance (NEN-EN-IEC 61386)			Flexibility	Resistance		Approvals		Protection Class	Page
			Min.	Max.	Compr.	Impact	Tensile		UV	Oil				
 EF-M Grey/ Black	Galvanised steel	PVC-RoHS	-20	+60	3 (750N)	4 (6J)	4 (1000N)	++	+++	+++			IP 67	3-02 3-03
 EF Grey	Galvanised steel	PVC-RoHS	-25	+70	4 (1250N)	4 (6J)	4 (1000N)	+++	+++	+++			IP 67	3-04
 EF Black	Galvanised steel	PVC-RoHS	-25	+70	4 (1250N)	4 (6J)	4 (1000N)	+++	+++	+++			IP 67	3-05
 OR Black	Galvanised steel	PVC-RoHS	-15	+100	4 (1250N)	4 (6J)	4 (1000N)	+++	++++	++++			IP 67	3-06
 OR Blue	Galvanised steel	PVC-RoHS	-15	+100	4 (1250N)	4 (6J)	4 (1000N)	+++	++++	++++			IP 67	3-07
 HC Black	Galvanised steel	PVC-RoHS	-45	+105	4 (1250N)	4 (6J)	4 (1000N)	+++	++++	++++			IP 67	3-08
 HCX Black	Galvanised steel	TPE-RoHS	-55	+145	4 (1250N)	4 (6J)	4 (1000N)	++++	+++	++			IP 67	3-09
 HFX Black	Galvanised steel	TPU Halogen-free RoHS	-55	+105	4 (1250N)	4 (6J)	4 (1000N)	++++	++++	++++			IP 67	3-10
 HFX Blue	Galvanised steel	TPU Halogen-free RoHS	-55	+105	4 (1250N)	4 (6J)	4 (1000N)	++++	++++	++++			IP 67	3-11
 HFX-V0 Black	Galvanised steel	TPU Halogen-free RoHS	-50	+105	4 (1250N)	4 (6J)	4 (1000N)	++++	++++	++++			IP 67	3-12
 ZHLS Black	Galvanised steel	Polyolefin Halogen-free RoHS	-25	+80	4 (1250N)	4 (6J)	4 (1000N)	+++	++++	++			IP 67	3-13
 HTDL Black	Galvanised steel	PVC-RoHS	-45	+105	4 (1250N)	4 (6J)	4 (1000N)	+++	++++	++++	 		IP 67	3-14
 HTUA Grey	Galvanised steel	PVC-RoHS	-45	+105	4 (1250N)	4 (6J)	4 (1000N)	+++	++++	++++	 		IP 67	3-15
 ZHUA Black	Galvanised steel	TPU Halogen-free RoHS	-55	+80	4 (1250N)	4 (6J)	4 (1000N)	++++	++++	++++			IP 67	3-16

The fittings for Sealtite are outlined in chapter 5 (pages 1 till 29).

