



ANAMET FITTINGS

LIQUID-TIGHT FITTINGS FOR SEALTITE IP 67



Anamet zinc diecast fitting for Anaconda Sealtite.

The zinc diecast Anamet fittings are especially for the large sizes Anaconda Sealtite (with exception of CNP). This Anamet fitting offers good corrosion protection in combination with a smooth appearance.



Material & Construction:


Construction: Zinc diecast fitting, consisting of 4 parts (counter nut, clamping ring, ferrule and body).

Material: Counter nut and body are zinc diecasted, ferrule is steel plated. Clamping rings are from PA6.

Temperature: -40 °C till +125 °C continuous.


Protection class: IP 67 (dust-proof, water-tight).

Colour: Metal.




ISO straight fitting, male, zinc diecast

Thread	Sealtite Size (inch)	Min. Internal Bore (mm)	Dimensions in mm					Standard Package	Article Number	Weight (Kg/100)
			A	B	C	D	E			
M50 x 1,5	1.1/2"	37,5	47	15	59	-	57	2	293.040.0	21,6
M63 x 1,5	2"	48,5	55	19	74	-	73	2	293.050.0	34,0



NPT straight fitting, male, zinc diecast

Thread	Sealtite Size (inch)	Min. Internal Bore (mm)	Dimensions in mm					Standard Package	Article Number	Weight (Kg/100)
			A	B	C	D	E			
NPT 2.1/2"	2.1/2"	61,0	71	24	90	-	86	1	294.063.0	67,4
NPT 3"	3"	74,0	75	26	108	-	104	1	294.075.0	96,6
NPT 4"	4"	95,0	80	28	134	-	128	1	294.099.0	125,0



NPT 90° fitting, male, zinc diecast

Thread	Sealtite Size (inch)	Min. Internal Bore (mm)	Dimensions in mm					Standard Package	Article Number	Weight (Kg/100)
			A	B	C	D	E			
NPT 2.1/2"	2.1/2"	61,0	86	24	90	104	86	1	294.963.0	117,8
NPT 3"	3"	74,0	98	26	108	112	104	1	294.975.0	172,8
NPT 4"	4"	95,0	112	28	134	127	128	1	294.999.0	278,6

