





Durchgangsbohrungen f. Kabelverschraubungen / through holes for cable glands



| Gew inde thread | Steigung pitch | D1 AußenØ outer diameter | D2 KernØ inner diameter | Durchgangsbohrung through hole |
|--------------------|-------------------|-----------------------------|----------------------------|-----------------------------------|
| M 6 | 1 | 6 | 5,00 | 6,5 |
| M 8 | 1,25 | 8 | 6,75 | 8,5 |
| M 10 | 1,5 | 10 | 8,50 | 10,5 |
| M 12 | 1,5 | 12 | 10,50 | 12,5 |
| M 16 | 1,5 | 16 | 14,50 | 16,5 |
| M 20 | 1,5 | 20 | 18,50 | 20,5 |
| M 25 | 1,5 | 25 | 23,50 | 25,5 |
| M 32 | 1,5 | 32 | 30,50 | 32,5 |
| M 40 | 1,5 | 40 | 38,50 | 40,5 |
| M 50 | 1,5 | 50 | 48,50 | 50,5 |
| M 63 | 1,5 | 63 | 61,50 | 63,5 |
| M 72 | 1,5 | 72 | 70,00 | 72,5 |
| M 75 | 1,5 | 75 | 73,50 | 75,5 |
| M 80 | 2 | 80 | 78,00 | 80,5 |
| M 85 | 2 | 85 | 83,00 | 85,5 |
| M 90 | 2 | 90 | 88,00 | 90,5 |
| M 100 | 2 | 100 | 98,00 | 100,5 |



| Gew inde thread | Steigung pitch | D1 AußenØ outer diameter | D2 KernØ inner diameter | Durchgangsbohrung through hole |
|--------------------|-------------------|-----------------------------|----------------------------|-----------------------------------|
| PG 7 | 1,270 | 12,50 | 11,28 | 12,7 |
| PG 9 | 1,410 | 15,20 | 13,86 | 15,4 |
| PG 11 | 1,410 | 18,60 | 17,26 | 18,8 |
| PG 13,5 | 1,410 | 20,40 | 19,06 | 20,7 |
| PG 16 | 1,410 | 22,50 | 21,16 | 22,8 |
| PG 21 | 1,588 | 28,30 | 26,78 | 28,6 |
| PG 29 | 1,588 | 37,00 | 35,48 | 37,4 |
| PG 36 | 1,588 | 47,00 | 45,48 | 47,5 |
| PG 42 | 1,588 | 54,00 | 52,48 | 54,5 |
| PG 48 | 1,588 | 59,30 | 57,78 | 59,8 |



| Gew inde thread | Steigung pitch | D1 AußenØ outer diameter | D2 KernØ inner diameter | Durchgangsbohrung through hole |
|--------------------|-------------------|-----------------------------|----------------------------|-----------------------------------|
| NPT 1/16" | 0,941 | 7,938 | 6,888 | 8,3 |
| NPT 1/8" | 0,941 | 10,287 | 9,233 | 10,7 |
| NPT 1/4" | 1,411 | 13,716 | 12,126 | 14,1 |
| NPT 3/8" | 1,411 | 17,145 | 15,545 | 17,4 |
| NPT 1/2" | 1,814 | 21,336 | 19,264 | 21,6 |
| NPT 3/4" | 1,814 | 26,67 | 24,579 | 27,0 |
| NPT 1" | 2,209 | 33,401 | 30,826 | 33,7 |
| NPT 1 1/4" | 2,209 | 42,164 | 39,551 | 42,5 |
| NPT 1 1/2" | 2,209 | 48,26 | 45,621 | 48,7 |
| NPT 2" | 2,209 | 60,325 | 57,633 | 60,7 |
| NPT 2 1/2" | 3,175 | 73,025 | 69,076 | 74,0 |
| NPT 3" | 3,175 | 88,9 | 84,852 | 89,8 |
| NPT 3 1/2" | 3,175 | 101,6 | 97,473 | 102,0 |
| NPT 4" | 3,175 | 114,3 | 110,093 | 114,8 |



| Gew inde thread | Steigung pitch | D1 AußenØ outer diameter | D2 KernØ inner diameter | Durchgangsbohrung through hole |
|--------------------|-------------------|-----------------------------|----------------------------|-----------------------------------|
| G 1/8" | 0,907 | 9,728 | 8,566 | 10 |
| G 1/4" | 1,337 | 13,157 | 11,445 | 13,4 |
| G 3/8" | 1,337 | 16,662 | 14,950 | 17 |
| G 1/2" | 1,814 | 20,955 | 18,631 | 21,3 |
| G 3/4" | 1,814 | 26,441 | 24,117 | 26,8 |
| G 1" | 2,309 | 33,249 | 30,291 | 33,7 |
| G 1 1/4" | 2,309 | 41,910 | 38,952 | 42,3 |
| G 1 1/2" | 2,309 | 47,803 | 44,845 | 48,1 |
| G 1 3/4" | 2,309 | 53,746 | 50,788 | 54,1 |
| G 2" | 2,309 | 59,614 | 56,656 | 60,1 |
| G 2 1/2" | 2,309 | 75,184 | 72,226 | 75,7 |
| G 3" | 2,309 | 87,884 | 84,926 | 88,4 |
| G 3 1/2" | 2,309 | 100,330 | 97,372 | 100,7 |
| G 4" | 2,309 | 113,030 | 110,072 | 113,7 |

