





# Durchgangsbohrungen f. Kabelverschraubungen / through holes for cable glands



Gew inde thread	Steigung pitch	D1 AußenØ outer diameter	D2 KernØ inner diameter	Durchgangsbohrung through hole
M 6	1	6	5,00	6,5
M 8	1,25	8	6,75	8,5
M 10	1,5	10	8,50	10,5
M 12	1,5	12	10,50	12,5
M 16	1,5	16	14,50	16,5
M 20	1,5	20	18,50	20,5
M 25	1,5	25	23,50	25,5
M 32	1,5	32	30,50	32,5
M 40	1,5	40	38,50	40,5
M 50	1,5	50	48,50	50,5
M 63	1,5	63	61,50	63,5
M 72	1,5	72	70,00	72,5
M 75	1,5	75	73,50	75,5
M 80	2	80	78,00	80,5
M 85	2	85	83,00	85,5
M 90	2	90	88,00	90,5
M 100	2	100	98,00	100,5



Gew inde thread	Steigung pitch	D1 AußenØ outer diameter	D2 KernØ inner diameter	Durchgangsbohrung through hole
PG 7	1,270	12,50	11,28	12,7
PG 9	1,410	15,20	13,86	15,4
PG 11	1,410	18,60	17,26	18,8
PG 13,5	1,410	20,40	19,06	20,7
PG 16	1,410	22,50	21,16	22,8
PG 21	1,588	28,30	26,78	28,6
PG 29	1,588	37,00	35,48	37,4
PG 36	1,588	47,00	45,48	47,5
PG 42	1,588	54,00	52,48	54,5
PG 48	1,588	59,30	57,78	59,8



Gew inde thread	Steigung pitch	D1 AußenØ outer diameter	D2 KernØ inner diameter	Durchgangsbohrung through hole
NPT 1/16"	0,941	7,938	6,888	8,3
NPT 1/8"	0,941	10,287	9,233	10,7
NPT 1/4"	1,411	13,716	12,126	14,1
NPT 3/8"	1,411	17,145	15,545	17,4
NPT 1/2"	1,814	21,336	19,264	21,6
NPT 3/4"	1,814	26,67	24,579	27,0
NPT 1"	2,209	33,401	30,826	33,7
NPT 1 1/4"	2,209	42,164	39,551	42,5
NPT 1 1/2"	2,209	48,26	45,621	48,7
NPT 2"	2,209	60,325	57,633	60,7
NPT 2 1/2"	3,175	73,025	69,076	74,0
NPT 3"	3,175	88,9	84,852	89,8
NPT 3 1/2"	3,175	101,6	97,473	102,0
NPT 4"	3,175	114,3	110,093	114,8



Gew inde thread	Steigung pitch	D1 AußenØ outer diameter	D2 KernØ inner diameter	Durchgangsbohrung through hole
G 1/8"	0,907	9,728	8,566	10
G 1/4"	1,337	13,157	11,445	13,4
G 3/8"	1,337	16,662	14,950	17
G 1/2"	1,814	20,955	18,631	21,3
G 3/4"	1,814	26,441	24,117	26,8
G 1"	2,309	33,249	30,291	33,7
G 1 1/4"	2,309	41,910	38,952	42,3
G 1 1/2"	2,309	47,803	44,845	48,1
G 1 3/4"	2,309	53,746	50,788	54,1
G 2"	2,309	59,614	56,656	60,1
G 2 1/2"	2,309	75,184	72,226	75,7
G 3"	2,309	87,884	84,926	88,4
G 3 1/2"	2,309	100,330	97,372	100,7
G 4"	2,309	113,030	110,072	113,7

